



Technical features

Common features

MATERIAL TYPE: EXTRUDED ALUMINIUM ANODIZED  
FRONT GLASS: 8MM THICKNESS TEMPERED  
HANDLE/GRIP: REVERSIBLE, GUN/HANDLE TYPE

### **LB 20-60**

cod. 593-A

Power supply: 12v, 3A  
Lamps: 20 - 50 W  
Burn time: 20' (50W)  
Weight (on air): 1.8 Kg  
Weight (underwater): 0.200 Kg  
Length: 138 mm  
Diameter: 100 mm

### **LB 20-180**

cod. 693

CHECK BATTERY LEVEL: BY DIODE ON THE TOP GUIDE  
ON OFF MODE: ELECTROMAGNETIC TYPE, NO PORT  
BATTERY PACK: 10 AMP. NiMh INTERCHANGEABLE  
BATTERY CONTROL: BY MINIATURIZED ELECTRONIC BOARD, TEMPERATURE/DISCHARGE  
BULBS USABLE: ALOGEN G6 FROM 35/50/75/100/150W 3500°K  
BURN TIME: 50WATT = 140 MINUTES  
GAS SECURITY: MECHANICAL GAS VALVE  
REFLECTING ELEMENTS WIDE LIGHT 80° - MEDIUM WIDE 40° - SPOT 10°  
(QUARTZ TREATMENT)  
USE: VIDEO/EXPLORATIONS  
DEPTH RATING: 450 FEET

**LH 20-180**

cod. 793

Power supply: 12v, 10 A  
Lamps: 20 - 150 W  
Burn time: 80' (100W)  
Weight (on air): 3,6 Kg  
Weight (in water): 0,9 Kg with 5A battery pack  
Length: 282 mm  
Diameter: 100 mm